



MANUFACTURER OF INDUSTRIAL
AUTOMATION PRODUCTS

تولید کننده محصولات
اتوماسیون صنعتی



www.green.ir

2027-Q1



Multifunction
Analog Timer Relay

MODEL GLIT-MT35A/30

مولتی تایمر

آنالوگ

GREEN LINE INDUSTRIAL TIME CONTROL
تجهیزات کنترل زمان



Scan For More Information

Specifications:

Type: Multifunction Analog Timer Relay
Model: GLIT-MT35A/30
Operating Voltage: 180 - 250V AC
Operating Frequency: 50-60 Hz
Output Current Max: 10A
Max Power: 2500W
Time Range: 1s - 30m
Timer Operation: Timer
Operational Temperature: -20°C to +50°C
Operating Relative Humidity: ≤70%
Display: N/A
Dimension (LxWxH): 66x36x86mm
Net Weight: 96g
Color: White/Black
Case Material: Flame Retardant ABS-PC
IP Degree of Protection: IP30
GREEN Guarantee: 24 Months

Multifunction
Analog Timer Relay

MODEL GLIT-MT35A/60

مولتی تایمر

آنالوگ

GREEN LINE INDUSTRIAL TIME CONTROL
تجهیزات کنترل زمان



Scan For More Information

Specifications:

Type: Multifunction Analog Timer Relay
Model: GLIT-MT35A/60
Operating Voltage: 180 - 250V AC
Operating Frequency: 50-60 Hz
Output Current Max: 10A
Max Power: 2500W
Time Range: 1s - 60m
Timer Operation: Timer
Operational Temperature: -20°C to +50°C
Operating Relative Humidity: ≤70%
Display: N/A
Dimension (LxWxH): 66x36x86mm
Net Weight: 96g
Color: White/Black
Case Material: Flame Retardant ABS-PC
IP Degree of Protection: IP30
GREEN Guarantee: 24 Months

Multifunction
Digital Timer Relay

MODEL GLIT-MT35D

مولتی تایمر

دیجیتال

GREEN LINE INDUSTRIAL TIME CONTROL
تجهیزات کنترل زمان



Scan For More Information

Specifications:

Type: Multifunction Digital Timer Relay
Model: GLIT-MT35D
Operating Voltage: 180 - 250V AC
Operating Frequency: 50-60 Hz
Output Current Max: 10A
Max Power: 2500W
Time Range: 0.01s - 9999 H
Timer Operation: Timer/Flasher
Operational Temperature: -20°C to +50°C
Operating Relative Humidity: ≤70%
Display: 4+1digit, 7-segment
Dimension (LxWxH): 66x36x86mm
Net Weight: 98g
Color: White/Black
Case Material: Flame Retardant ABS-PC
IP Degree of Protection: IP30
GREEN Guarantee: 24 Months

Digital Astronomical
Time Switch

MODEL GLIT-TC35D

ساعت نجومی

دیجیتال

GREEN LINE INDUSTRIAL TIME CONTROL
تجهیزات کنترل زمان



Scan For More Information

Specifications:

Type: Digital Astronomical Time Switch
Model: GLIT-TC35D
Operating Voltage: 180 - 250V AC
Operating Frequency: 50-60 Hz
Output Current Max: 10A
Max Power: 2500W
RTC Battery Backup Life: 5 Years
RTC Battery Backup Voltage: 3V
Operational Temperature: -20°C to +50°C
Operating Relative Humidity: ≤70%
Display: 4+1digit, 7-segment
Dimension (LxWxH): 66x36x86mm
Net Weight: 98g
Color: White/Black
Case Material: Flame Retardant ABS-PC
IP Degree of Protection: IP30
GREEN Guarantee: 24 Months



شرکت پردیس صنعت سیاره سبز

دفتر مرکزی: تهران، خیابان سمیه، بین خیابان سپهبد قرنی و استاد نجات الهی، شماره 215
ساختمان سبز
تلفن: 021-58132000
فکس: 021-88808171
www.green.ir

دفتر گارانتی: تهران، خیابان سمیه، بین خیابان سپهبد قرنی و استاد نجات الهی، شماره 215
ساختمان سبز، طبقه همکف
تلفن: 021-88170017
فکس: 021-88808171
www.green-guarantee.ir

کارخانه: سنجان، شهرک صنعتی سنجان، خیابان خلیج فارس، خیابان بهمن
کارخانه سبز
تلفن: 025-33673970-78
فکس: 025-33673979

GREEN PLANET CO.

GREEN Planet Co. Headquarter: No. 215, Between Gharani Ave & Nejatollahi St.,
Somayeh St., Tehran, IRAN
Headquarter: +98 21 58132000
www.green.ir

Fax: +98 21 88808171

GREEN Planet Co. Guarantee: No. 215, Between Gharani Ave & Nejatollahi St.,
Somayeh St., Tehran, IRAN
GREEN Guarantee: +98 21 8817 0017
www.green-guarantee.ir

Fax: +98 21 88808171

GREEN Planet Co. Factory: GREEN Factory, Bahman Ave, Khalijefars St.,
Salafchegan Industrial Park, Qom, IRAN
GREEN Factory: +98 25 3367 3970 - 78
Fax: +98 25 3367 3979

Single-Phase Analog
Voltage Control Relay

MODEL GLIP-SV35A

کنترل ولتاژ

تک فاز آنالوگ

GREEN LINE INDUSTRIAL PROTECTORS

تجهیزات حفاظتی



Specifications:

Type: Single-Phase Analog Voltage Control Relay
Model: GLIP-SV35A
Operating Voltage: 180 - 250V AC
Operating Frequency: 50-60 Hz
Output Current Max: 10A
Max Power: 2500W
Under voltage Cut-Off: 150 - 210 V AC
Over voltage Cut-Off: 230 - 290 V AC
On Time: 10 s
Off Time: 1 - 60 s
Operational Temperature: -20°C to +50°C
Operating Relative Humidity: ≤70%
Display: N/A
Dimension (LxWxH): 66x36x86mm
Net Weight: 104g
Color: White/Black
Case Material: Flame Retardant ABS-PC
IP Degree of Protection: IP30
GREEN Guarantee: 24 Months



Scan For More Information

Single-Phase Digital
Voltage Control Relay

MODEL GLIP-SV35D

کنترل ولتاژ

تک فاز دیجیتال

GREEN LINE INDUSTRIAL PROTECTORS

تجهیزات حفاظتی



Specifications:

Type: Single-Phase Digital Voltage Control Relay
Model: GLIP-SV35D
Operating Voltage: 180 - 250V AC
Operating Frequency: 50-60 Hz
Output Current Max: 10A
Max Power: 2500W
Under voltage Cut-Off: 150 - 210 V AC
Over voltage Cut-Off: 230 - 300 V AC
On Time: 1 - 240 S
Off Time: 1 - 60 S
Operational Temperature: -20°C to +50°C
Operating Relative Humidity: ≤70%
Display: 3+1digit, 7-segment
Dimension (LxWxH): 66x36x86mm
Net Weight: 102g
Color: White/Black
Case Material: Flame Retardant ABS-PC
IP Degree of Protection: IP30
GREEN Guarantee: 24 Months



Scan For More Information

Analog
Phase Control Relay

MODEL GLIP-TP35A

کنترل فاز

آنالوگ

GREEN LINE INDUSTRIAL PROTECTORS

تجهیزات حفاظتی



Specifications:

Type: Analog Phase Control Relay
Model: GLIP-TP35A
Operating Voltage: 180 - 250V AC
Operating Frequency: 50-60 Hz
Output Current Max: 10A
Max Power: 2500W
Voltage Cut-Off: 220 x ΔU%
On Time: 10 s
Off Time: 1 - 60 s
Operational Temperature: -20°C to +50°C
Operating Relative Humidity: ≤70%
Asymmetric: 5-30 %
Display: N/A
Dimension (LxWxH): 66x36x86mm
Net Weight: 104g
Color: White/Black
Case Material: Flame Retardant ABS-PC
IP Degree of Protection: IP30
GREEN Guarantee: 24 Months



Scan For More Information

Digital
Phase Control Relay

MODEL GLIP-TP35D

کنترل فاز

دیجیتال

GREEN LINE INDUSTRIAL PROTECTORS

تجهیزات حفاظتی



Specifications:

Type: Digital Phase Control Relay
Model: GLIP-TP35D
Operating Voltage: 180 - 250V AC
Operating Frequency: 50-60 Hz
Output Current Max: 10A
Max Power: 2500W
Under voltage Cut-Off: 150 - 210 V AC
Over voltage Cut-Off: 230 - 300 V AC
On Time: 1 - 240 S
Off Time: 1 - 60 S
Operational Temperature: -20°C to +50°C
Operating Relative Humidity: ≤70%
Asymmetric: 5-30 %
Display: 3+1digit, 7-segment
Dimension (LxWxH): 66x36x86mm
Net Weight: 102g
Color: White/Black
Case Material: Flame Retardant ABS-PC
IP Degree of Protection: IP30
GREEN Guarantee: 24 Months



Scan For More Information

3-Phase Analog
Voltage Control Relay

MODEL GLIP-TV35A

کنترل ولتاژ

سه فاز آنالوگ

GREEN LINE INDUSTRIAL PROTECTORS

تجهیزات حفاظتی



Specifications:

Type: 3-Phase Analog Voltage Control Relay
Model: GLIP-TV35A
Operating Voltage: 180 - 250V AC
Operating Frequency: 50-60 Hz
Output Current Max: 10A
Max Power: 2500W
Under voltage Cut-Off: 150 - 210 V AC
Over voltage Cut-Off: 230 - 290 V AC
On Time: 10 S
Off Time: 1 - 60 S
Operational Temperature: -20°C to +50°C
Operating Relative Humidity: ≤70%
Voltage Display: N/A
Dimension (LxWxH): 66x36x86mm
Net Weight: 104g
Color: White/Black
Case Material: Flame Retardant ABS-PC
IP Degree of Protection: IP30
GREEN Guarantee: 24 Months



Scan For More Information

3-Phase Digital
Voltage Control Relay

MODEL GLIP-TV35D

کنترل ولتاژ

سه فاز دیجیتال

GREEN LINE INDUSTRIAL PROTECTORS

تجهیزات حفاظتی



Specifications:

Type: 3-Phase Digital Voltage Control Relay
Model: GLIP-TV35D
Operating Voltage: 180 - 250V AC
Operating Frequency: 50-60 Hz
Output Current Max: 10A
Max Power: 2500W
Under voltage Cut-Off: 150 - 210 V AC
Over voltage Cut-Off: 230 - 300 V AC
On Time: 1 - 240 S
Off Time: 1 - 60 S
Operational Temperature: -20°C to +50°C
Operating Relative Humidity: ≤70%
Display: 3+1digit, 7-segment
Dimension (LxWxH): 66x36x86mm
Net Weight: 102g
Color: White/Black
Case Material: Flame Retardant ABS-PC
IP Degree of Protection: IP30
GREEN Guarantee: 24 Months



Scan For More Information